



ENERG Y UA enepγus · ενεργεια IE IA



NIBE F1345-30

35 °C

















A++

 A^+

A

B

C

D

E

F

G



2015

811/2013



IJA ENERG енергия · ενεργεια



NIBE F1345-30

































B



Supplier's name:	NI	BE	
Model:	NIBE F	1345-30	
Temperature application	35	55	°C
Declared load profile for water			
heating		1	
Seasonal space heating energy	A++	A++	
efficiency class, average climate:		7	
Water heating energy efficiency			
class, average climate:		Π	
Rated heat output, average climate:	35	35	kW
Annual energy consumption for	15539	19880	kWh
space heating, average climate		10000	
Annual electricity consumption for			kWh
water heating, average climate		r	
Seasonal space heating energy	178	178 137	
efficiency, average climate:			
Water heating energy efficiency,			%
average climate:		<u> </u>	-ID
Sound power level LWA indoors		17 I	dB
Rated heat output, cold climate:	35	35	kW
Rated heat output, warm climate:	35	35	kW
Annual energy consumption for	17817	22770	kWh
space heating, cold climate			
Annual electricity consumption for water heating, cold climate			kWh
Annual energy consumption for			
space heating, warm climate	10063	12803	kWh
Annual electricity consumption for			
water heating, warm climate			kWh
Seasonal space heating energy	106	144	0/
efficiency, cold climate:	186	144	%
Water heating energy efficiency, cold			%
climate:			70
Seasonal space heating energy	178	138	%
efficiency, warm climate:	170	100	/
Water heating energy efficiency,			%
warm climate:			, , ,
Sound power level LWA outdoors		-	dB

Data for package fiche

Controller class		I	
Controler contribution to efficiency		2	%
Seasonal space heating energy efficiency of package, average climate:	180	139	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A++	%
Seasonal space heating energy efficiency of package, cold climate:	188	146	%
Seasonal space heating energy efficiency of package, warm climate:	180	140	%

Model(s):			NIE	BE F1345-30			
Type of heat source/sink:			Brii	ne-to-water			
Low-temperature heat pump:				No	-		
Equipped with supplementary heater:				No			- K)
Heat pump combination heater:				No	T A T		
Climate condition:				Average			
Temperature application:			Medium te	emperature (55 °C)			
Applied standards: EN14825							
				Seasonal space heating energy			
Rated heat output	Prated	35,0	kW	efficiency	η_{s}	137	%
Declared capacity for part load at outdoor ten	nperature Ti			Declared coefficient of performance for po	art load at outdoo	or temperatu	re Ti
Tj = -7 °C	Pdh	29,5	kW	Tj = -7 °C	COPd	3,15	kW
Tj = +2 °C	Pdh	30,2	kW	Tj = +2 °C	COPd	3,64	kW
Tj = +7 °C	Pdh	15,3	kW	Tj = +7 °C	COPd	4,09	kW
Tj = +12 °C	Pdh	15,4	kW	Tj = +12 °C	COPd	4,40	kW
Tj = biv	Pdh	29,6	kW	Tj = biv	COPd	3,23	kW
Tj = TOL	Pdh	29,3	kW	Tj = TOL	COPd	2,99	kW
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)	COPd		kW
Bivalent temperature	T _{biv}	-6	°C	Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych	-	kW	Cycling interval efficiency	COPcyc		
Degradation co-efficient	Cdh	0,99	-	Heating water operating limit	WTOL	65	°C
Power consumption in modes other than activ	ie mode			Supplementary heater			
Off mode	P _{OFF}	0,002	kW	Rated heat output	Psup	5,7	kW
Thermostat-off mode	P _{TO}	0,04	kW	·		<u> </u>	ı
Standby mode	P _{SB}	0,007	kW	Type of energy input		Electric	
Crankcase heater mode	P _{CK}	0,07	kW				
Other items							
Constitution of the consti				Data da inflammata, antida ana	1 1		3 /1-

Rated air flow rate, outdoors

Rated brine or water flow rate,

Water heating energy efficiency

outdoor heat exchanger

Daily fuel consumption

Annual fuel consumption

exchanger

Rated water flow rate, indoor heat

m³/h

m³/h

m³/h

%

kWh

GJ

3,15

5,83

 η_{wh}

 \mathbf{Q}_{fuel}

AFC

Annual electricity consumption

Approved by:

Capacity control

Sound power level, indoors/outdoors

Annual energy consumption

For heat pump combination heater:

Declared load profile

Daily electricity consumption

Contact details © NIBE Energy Systems - Box 14 - Hannabadsvägen 5 - 28521 Markaryd - Sweden

dB

kWh

kWh

kWh

variable

47/-

19880

 $L_{\underline{WA}}$

 \mathbf{Q}_{HE}

 $\mathbf{Q}_{\mathrm{elec}}$

AEC